

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006

Issue date: 07/01/2022 Revision date: 04/03/2025 Supersedes version of: 04/05/2023 Version: 1.4

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form : Mixture

Product name : ORGANIC APPLE FLAVOUR PO-0509

UFI : E7TU-NHJ1-TG17-DX4E
Product code : POMM-PO0509

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

Main use category : Industrial use, Professional use

#### 1.3. Details of the supplier of the safety data sheet

SELECTAROME SAS 45 Bd Marcel Pagnol PA Aromagrasse FR 06130 GRASSE France

T+33 4.93.36.22.22, F 04.93.40.71.72

reglementaire@selectarome.com

### 1.4. Emergency telephone number

Country/Area	Organisation/Company	Address	Emergency number	Comment
France	ORFILA		+33 1 45 42 59 59	This number provides contact details for all French anti-poison centres. These anti-poison and toxicovigilance centres provide free medical assistance (excluding call costs), 24 hours a day, 7 days a week.

### SECTION 2: Hazards identification

## 2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]
Flammable liquids, Category 2 H225
Serious eye damage/eye irritation, Category 2 H319

Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects Highly flammable liquid and vapour. Causes serious eye irritation.

## 2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :





GHS02

GHS07

Signal word (CLP) : Danger

Hazard statements (CLP) : H225 - Highly flammable liquid and vapour.

H319 - Causes serious eye irritation.

Precautionary statements (CLP) : P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

### Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006

P280 - Wear protective gloves, protective clothing, eye protection. P337+P313 - If eye irritation persists: Get medical advice/attention.

#### 2.3. Other hazards

Contains no PBT and/or vPvB substances ≥ 0.1% assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

## **SECTION 3: Composition/information on ingredients**

#### 3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
ethanol/ ethyl alcohol substance with national workplace exposure limit(s) (FR)	CAS-No.: 64-17-5 EC-No.: 200-578-6 EC Index-No.: 603-002-00-5	25 – 50	Flam. Liq. 2, H225 Eye Irrit. 2, H319
isopentyl acetate substance with national workplace exposure limit(s) (FR); substance with a Community workplace exposure limit	CAS-No.: 123-92-2 EC-No.: 204-662-3 EC Index-No.: 607-130-00-2 REACH-no: 01-2119548408- 32	< 0,1	Flam. Liq. 3, H226 EUH066
Ethyl acetate substance with national workplace exposure limit(s) (FR); substance with a Community workplace exposure limit	CAS-No.: 141-78-6 EC-No.: 205-500-4 EC Index-No.: 607-022-00-5	< 0,1	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336 EUH066
Acetic acid substance with national workplace exposure limit(s) (FR); substance with a Community workplace exposure limit	CAS-No.: 64-19-7 EC-No.: 200-580-7 EC Index-No.: 607-002-00-6	< 0,1	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 (ATE=1060 mg/kg bodyweight) Skin Corr. 1A, H314 Eye Dam. 1, H318
Isoamyl alcohol substance with national workplace exposure limit(s) (FR); substance with a Community workplace exposure limit	CAS-No.: 123-51-3 EC-No.: 204-633-5	< 0,1	Flam. Liq. 3, H226 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H335
n-butyl acetate substance with national workplace exposure limit(s) (FR); substance with a Community workplace exposure limit	CAS-No.: 123-86-4 EC-No.: 204-658-1 EC Index-No.: 607-025-00-1	< 0,1	Flam. Liq. 3, H226 STOT SE 3, H336 EUH066

Specific concentration limits:		
Name	Product identifier	Specific concentration limits (%)
Acetic acid	CAS-No.: 64-19-7 EC-No.: 200-580-7 EC Index-No.: 607-002-00-6	$(10 \le C < 25)$ Skin Irrit. 2; H315 $(10 \le C < 25)$ Eye Irrit. 2; H319 $(25 \le C < 90)$ Skin Corr. 1B; H314 $(90 \le C \le 100)$ Skin Corr. 1A; H314

Full text of H- and EUH-statements: see section 16

### Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006

#### **SECTION 4: First aid measures**

#### 4.1. Description of first aid measures

First-aid measures general : If you feel unwell, seek medical advice.

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.

First-aid measures after skin contact : Rinse skin with water/shower. Take off immediately all contaminated clothing.

First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and

easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

First-aid measures after ingestion : Call a poison center or a doctor if you feel unwell.

First-aid measures for first aider : First aid workers will be equipped with suitable personal protective equipment.

#### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation : None under normal conditions.
Symptoms/effects after skin contact : None under normal conditions.

Symptoms/effects after eye contact : Eye irritation.

Symptoms/effects after ingestion : None under normal conditions.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

#### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

Unsuitable extinguishing media : Do not use a heavy water stream.

#### 5.2. Special hazards arising from the substance or mixture

Fire hazard : Highly flammable liquid and vapour.

Explosion hazard : No direct explosion hazard.

Hazardous decomposition products in case of fire : Toxic fumes may be released.

#### 5.3. Advice for firefighters

Firefighting instructions : Fight fire from safe distance and protected location. Do not enter fire area without

proper protective equipment, including respiratory protection.

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained

breathing apparatus. Complete protective clothing.

#### **SECTION 6: Accidental release measures**

### 6.1. Personal precautions, protective equipment and emergency procedures

General measures : Stop leak if safe to do so. Notify authorities if product enters sewers or public waters.

Absorb spillage to prevent material damage.

For non-emergency personnel

Protective equipment : Wear recommended personal protective equipment.

Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid contact with

skin and eyes.

For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further

information refer to section 8: "Exposure controls/personal protection".

Emergency procedures : Evacuate unnecessary personnel. Stop leak if safe to do so.

## 6.2. Environmental precautions

Avoid release to the environment.

#### 6.3. Methods and material for containment and cleaning up

For containment : Absorb spilled material with sand or earth. Contain any spills with dikes or absorbents

to prevent migration and entry into sewers or streams. Stop leak without risks if

possible.

#### Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006

Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers

or public waters.

Other information : Dispose of materials or solid residues at an authorized site.

#### 6.4. Reference to other sections

For further information refer to section 13.

## **SECTION 7: Handling and storage**

#### 7.1. Precautions for safe handling

Additional hazards when processed : Not expected to present a significant hazard under anticipated conditions of normal

use.

Precautions for safe handling : Ensure good ventilation of the work station. Keep away from heat, hot surfaces, sparks,

open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapours may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Avoid contact with skin and

eyes.

Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling

the product.

#### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Ground/bond container and receiving equipment.

Storage conditions : Store in a well-ventilated place. Keep cool. Keep container tightly closed.

Packaging materials : Store always product in container of same material as original container.

**Switzerland** 

Storage class (LK) : LK 3 - Flammable liquids

#### 7.3. Specific end use(s)

No additional information available

### **SECTION 8: Exposure controls/personal protection**

## 8.1. Control parameters

National occupational exposure and biological limit values

Acetic acid (64-19-7)		
EU - Indicative Occupational Exposure Limit (IOEL)		
Local name	Acetic acid	
IOEL TWA	25 mg/m³	
	10 ppm	
IOEL STEL	50 mg/m <sup>3</sup>	
	20 ppm	
Regulatory reference COMMISSION DIRECTIVE (EU) 2017/164		
France - Occupational Exposure Limits		
Local name	Acide acétique	
VME (OEL TWA)	25 mg/m³	
	10 ppm	
VLE (OEL C/STEL)	50 mg/m <sup>3</sup>	
	20 ppm	
Remark	Valeurs règlementaires indicatives	
Regulatory reference	Arrêté du 30 juin 2004 modifié (réf.: INRS ED 6443, 2022; Outil65; Arrête du 27 septembre 2019)	

## Safety Data Sheet

18 mg/m²   5 ppm	Isoamyl alcohol (123-51-3)	
IOEL TWA 18 mg/m² 5 ppm IOEL STEL 27 mg/m² 10 ppm IOEL STEL 27 mg/m² 10 ppm IOEL STEL 27 mg/m² 10 ppm IOEL STEL 28 mg/m² 10 ppm IOEL STEL 29 mg/m² 10 ppm IOEL STEL 37 mg/m² 10 ppm IOEL TWA 30 ppm IOEL C/STEL) 29 mg/m² 10 ppm IOEL C/STEL) 37 mg/m² 10 ppm IOEL C/STEL) 37 mg/m² 10 ppm IOEL C/STEL) 47 mg/m² 10 ppm IOEL C/STEL) 57 mg/m² 10 ppm IOEL STEL 48 mg/m² 5 ppm IOEL TWA 58 mg/m² 10 ppm IOEL STEL 58 mg/m² 10 ppm IOEL STEL 58 mg/m² 10 ppm IOEL STEL 168 mg/m² 10 ppm IOEL STEL	EU - Indicative Occupational Exposure Limit (IOE	L)
Sppm	Local name	Isoamyl alcohol
Regulatory reference   COMMISSION DIRECTIVE (EU) 2019/1831	IOEL TWA	18 mg/m³
Regulatory reference COMMISSION DIRECTIVE (EU) 2019/1831  France - Occupational Exposure Limits  Local name Alcool Isoamylique  VME (OEL CYSTEL)  23 mg/m³  10 ppm  Remark Valeurs règlementaires contraignantes  Regulatory reference Article R4412-149 du Code du travail (réf.: INRS ED 6443, 2022; Outil65; Décret n° 2021-1849)  Ethyl acetate (141-78-6)  EU - Indicative Occupational Exposure Limit (IOEL)  Local name Ethyl acetate  IOEL TWA 734 mg/m³  200 ppm  IOEL STEL 468 mg/m³  400 ppm  Regulatory reference COMMISSION DIRECTIVE (EU) 2017/164  France - Occupational Exposure Limits  Local name Acétate d'éthyle  VME (OEL TWA) 734 mg/m³  200 ppm  VVE (OEL CYSTEL) 468 mg/m³  400 ppm  Regulatory reference COMMISSION DIRECTIVE (EU) 2017/164  France - Occupational Exposure Limits  Local name Acétate d'éthyle  VME (OEL TWA) 734 mg/m³  200 ppm  Remark Valeurs règlementaires contraignantes  Regulatory reference Article R4412-149 du Code du travail (réf.: INRS ED 6443, 2022; Outil65; Décret n° 2019-1487; Décret n° 2021-1546; Décret n° 2021-1849)  The Decret n° 2021-1849 (INRS ED 6443, 2022; Outil65; Décret n° 2019-1487; Décret n° 2021-1546; Décret n° 2021-1849)  EU - Indicative Occupational Exposure Limit (IOEL)  Local name n-Butyl acetate  IOEL TWA 241 mg/m³  50 ppm		5 ppm
Regulatory reference COMMISSION DIRECTIVE (EU) 2019/1831  France - Occupational Exposure Limits  Local name Alcool Isoamylique  VME (OEL CYSTEL)  23 mg/m³  10 ppm  Remark Valeurs règlementaires contraignantes  Regulatory reference Article R4412-149 du Code du travail (réf.: INRS ED 6443, 2022; Outil65; Décret n° 2021-1849)  Ethyl acetate (141-78-6)  EU - Indicative Occupational Exposure Limit (IOEL)  Local name Ethyl acetate  IOEL TWA 734 mg/m³  200 ppm  IOEL STEL 468 mg/m³  400 ppm  Regulatory reference COMMISSION DIRECTIVE (EU) 2017/164  France - Occupational Exposure Limits  Local name Acétate d'éthyle  VME (OEL TWA) 734 mg/m³  200 ppm  VVE (OEL CYSTEL) 468 mg/m³  400 ppm  Regulatory reference COMMISSION DIRECTIVE (EU) 2017/164  France - Occupational Exposure Limits  Local name Acétate d'éthyle  VME (OEL TWA) 734 mg/m³  200 ppm  Remark Valeurs règlementaires contraignantes  Regulatory reference Article R4412-149 du Code du travail (réf.: INRS ED 6443, 2022; Outil65; Décret n° 2019-1487; Décret n° 2021-1546; Décret n° 2021-1849)  The Decret n° 2021-1849 (INRS ED 6443, 2022; Outil65; Décret n° 2019-1487; Décret n° 2021-1546; Décret n° 2021-1849)  EU - Indicative Occupational Exposure Limit (IOEL)  Local name n-Butyl acetate  IOEL TWA 241 mg/m³  50 ppm	IOEL STEL	
Regulatory reference COMMISSION DIRECTIVE (EU) 2019/1831  France - Occupational Exposure Limits  Local name Alcool isoamylique  VME (OEL TWA) 18 mg/m³ 5 ppm  VVE (OEL C/STEL) 27 mg/m³ 10 ppm  Remark Valeurs règlementaires contraignantes  Regulatory reference Article R4412-149 du Code du travail (réf.: INRS ED 6443, 2022; Outil65; Décret n° 2021-1849)  Ethyl acetate (141-78-6)  EU - Indicative Occupational Exposure Limit (IOEL)  Local name Ethyl acetate  IOEL TWA 734 mg/m³ 200 ppm  IOEL STEL 168 mg/m³ 400 ppm  Regulatory reference COMMISSION DIRECTIVE (EU) 2017/164  France - Occupational Exposure Limits  Local name Acétate d'éthyle  VME (OEL C/STEL) 168 mg/m³ 200 ppm  VLE (OEL C/STEL) 168 mg/m³ 400 ppm  Remark Valeurs règlementaires contraignantes  Regulatory reference Article R4412-149 du Code du travail (réf.: INRS ED 6443, 2022; Outil65; Décret n° 2019-1487; Décret n° 2020-1546; Décret n° 2021-1849)  VLE (OEL C/STEL) 468 mg/m³ 400 ppm  Remark Valeurs règlementaires contraignantes  Regulatory reference Article R4412-149 du Code du travail (réf.: INRS ED 6443, 2022; Outil65; Décret n° 2019-1487; Décret n° 2020-1546; Décret n° 2021-1349; Décret n° 2021-1849)  N-butyl acetate (123-86-4)  EU - Indicative Occupational Exposure Limit (IOEL)  Local name n-Butyl acetate  IOEL TWA 241 mg/m³ 50 ppm		-
France - Occupational Exposure Limits  Local name	Regulatory reference	
Local name Alcool isoamylique  VME (OEL TWA) 18 mg/m³ 5 ppm  VLE (OEL C/STEL) 37 mg/m³ 10 ppm  Remark Valeurs règlementaires contraignantes  Regulatory reference Article R4412-149 du Code du travail (réf.: INRS ED 6443, 2022; Outil65; Décret n° 2021-1849)  Ethyl acetate (141-78-6)  EU - Indicative Occupational Exposure Limit (IOEL)  Local name Ethyl acetate  IOEL TWA 734 mg/m³ 200 ppm  IOEL STEL 1468 mg/m³ 400 ppm  Regulatory reference COMMISSION DIRECTIVE (EU) 2017/164  France - Occupational Exposure Limits  Local name Acétate d'éthyle  VIME (OEL TWA) 734 mg/m³ 200 ppm  VLE (OEL C/STEL) 1468 mg/m³ 400 ppm  Remark Acétate d'éthyle  VIME (OEL C/STEL) 1468 mg/m³ 400 ppm  Remark Valeurs règlementaires contraignantes  Regulatory reference Article R4412-149 du Code du travail (réf.: INRS ED 6443, 2022; Outil65; Décret n° 2019-1487; Décret n° 2020-1546; Décret n° 2021-1849)  In-butyl acetate (123-86-4)  EU - Indicative Occupational Exposure Limit (IOEL)  Local name n-Butyl acetate  IOEL TWA 241 mg/m³ 50 ppm		· , , , , , , , , , , , , , , , , , , ,
VLE (OEL C/STEL)  5 ppm  37 mg/m² 10 ppm  Remark  Valeurs règlementaires contraignantes  Regulatory reference Article R4412-149 du Code du travail (réf.: INRS ED 6443, 2022; Outil65; Décret n° 2021-1849)  Ethyl acetate (141-78-6)  EU - Indicative Occupational Exposure Limit (IOEL)  Local name Ethyl acetate IOEL TWA Tya mg/m² 200 ppm  IOEL STEL Adéa mg/m³ 400 ppm  Regulatory reference COMMISSION DIRECTIVE (EU) 2017/164  France - Occupational Exposure Limits  Local name Acétate d'éthyle  VME (OEL TWA) Tya mg/m² 200 ppm  VLE (OEL C/STEL) Adéa mg/m³ 400 ppm  Remark Valeurs règlementaires contraignantes  Regulatory reference Article R4412-149 du Code du travail (ref.: INRS ED 6443, 2022; Outil65; Décret n° 2019-1487; Décret n° 2020-1546; Décret n° 2021-1849)  n-butyl acetate (123-86-4)  EU - Indicative Occupational Exposure Limit (IOEL)  Local name N-Butyl acetate IOEL TWA Phylia acetate IOEL TWA INTERCATION Phylia Phylia acetate IOEL TWA Phylia acetate IOEL TWA INTERCATION Phylia IOEL TWA INTERCATION Phylia Phylia acetate IOEL TWA INTERCATION Phylia IOEL TWA INTERCATION Phylia IOEL TWA INTERCATION Phylia Phylia IOEL TWA INTERCATION Phylia Ph	Local name	Alcool isoamylique
VLE (OEL C/STEL)  5 ppm  37 mg/m² 10 ppm  Remark  Valeurs règlementaires contraignantes  Regulatory reference Article R4412-149 du Code du travail (réf.: INRS ED 6443, 2022; Outil65; Décret n° 2021-1849)  Ethyl acetate (141-78-6)  EU - Indicative Occupational Exposure Limit (IOEL)  Local name Ethyl acetate IOEL TWA Tya mg/m² 200 ppm  IOEL STEL Adéa mg/m³ 400 ppm  Regulatory reference COMMISSION DIRECTIVE (EU) 2017/164  France - Occupational Exposure Limits  Local name Acétate d'éthyle  VME (OEL TWA) Tya mg/m² 200 ppm  VLE (OEL C/STEL) Adéa mg/m³ 400 ppm  Remark Valeurs règlementaires contraignantes  Regulatory reference Article R4412-149 du Code du travail (ref.: INRS ED 6443, 2022; Outil65; Décret n° 2019-1487; Décret n° 2020-1546; Décret n° 2021-1849)  n-butyl acetate (123-86-4)  EU - Indicative Occupational Exposure Limit (IOEL)  Local name N-Butyl acetate IOEL TWA Phylia acetate IOEL TWA INTERCATION Phylia Phylia acetate IOEL TWA Phylia acetate IOEL TWA INTERCATION Phylia IOEL TWA INTERCATION Phylia Phylia acetate IOEL TWA INTERCATION Phylia IOEL TWA INTERCATION Phylia IOEL TWA INTERCATION Phylia Phylia IOEL TWA INTERCATION Phylia Ph	VME (OEL TWA)	18 mg/m³
NUE (OEL C/STEL)  37 mg/m³ 10 ppm  Remark  Valeurs règlementaires contraignantes  Article R4412-149 du Code du travail (réf.: INRS ED 6443, 2022; Outil65; Décret n° 2021-1849)  Ethyl acetate (141-78-6)  EU - Indicative Occupational Exposure Limit (IOEL)  Local name  Ethyl acetate  10EL TWA  200 ppm  IOEL STEL  468 mg/m³ 400 ppm  Regulatory reference  COMMISSION DIRECTIVE (EU) 2017/164  France - Occupational Exposure Limits  Local name  Acétate d'éthyle  VME (OEL TWA)  734 mg/m³ 200 ppm  VLE (OEL C/STEL)  468 mg/m³ 400 ppm  Regulatory reference  Acétate d'éthyle  VAIL (OEL C/STEL)  468 mg/m³ 400 ppm  Remark  Valeurs règlementaires contraignantes  Regulatory reference  Article R4412-149 du Code du travail (réf.: INRS ED 6443, 2022; Outil65; Décret n° 2019-1487; Décret n° 2020-1546; Décret n° 2021-434; Décret n° 2021-1849)  n-butyl acetate (123-86-4)  EU - Indicative Occupational Exposure Limit (IOEL)  Local name  n-Butyl acetate  IOEL TWA  241 mg/m³ 50 ppm		
Remark Valeurs règlementaires contraignantes Regulatory reference Article R4412-149 du Code du travail (réf.: INRS ED 6443, 2022; Outil65; Décret n° 2021-1849)  Ethyl acetate (141-78-6)  EU - Indicative Occupational Exposure Limit (IOEL) Local name Ethyl acetate IOEL TWA 734 mg/m³ 200 ppm  IOEL STEL 1468 mg/m³ 400 ppm Regulatory reference COMMISSION DIRECTIVE (EU) 2017/164  France - Occupational Exposure Limits Local name Acétate d'éthyle VME (OEL TWA) 734 mg/m³ 200 ppm  VLE (OEL C/STEL) 1668 mg/m³ 400 ppm  VLE (OEL C/STEL) 1688 mg/m³ 400 ppm  Remark Valeurs règlementaires contraignantes Regulatory reference Article R4412-149 du Code du travail (réf.: INRS ED 6443, 2022; Outil65; Décret n° 2019-1487; Décret n° 2020-1546; Décret n° 2021-434; Décret n° 2021-1849)  n-butyl acetate (123-86-4) EU - Indicative Occupational Exposure Limit (IOEL) Local name n-Butyl acetate IOEL TWA 241 mg/m³ 50 ppm	VLE (OEL C/STEL)	
Regulatory reference Article R4412-149 du Code du travail (réf.: INRS ED 6443, 2022; Outil65; Décret n° 2021-1849)  Ethyl acetate (141-78-6)  EU - Indicative Occupational Exposure Limit (IOEL) Local name Ethyl acetate IOEL TWA 734 mg/m³ 200 ppm  IOEL STEL 468 mg/m³ 400 ppm  Regulatory reference COCupational Exposure Limits Local name COCUMMISSION DIRECTIVE (EU) 2017/164  France - Occupational Exposure Limits Local name Acétate d'éthyle 734 mg/m³ 200 ppm  VME (OEL TWA) 734 mg/m³ 200 ppm  VLE (OEL C/STEL) 468 mg/m³ 400 ppm  Remark Valeurs règlementaires contraignantes Regulatory reference Article R4412-149 du Code du travail (réf.: INRS ED 6443, 2022; Outil65; Décret n° 2019-1487; Décret n° 2020-1546; Décret n° 2021-1349)  n-butyl acetate (123-86-4)  EU - Indicative Occupational Exposure Limit (IOEL) Local name n-Butyl acetate IOEL TWA 241 mg/m³ 50 ppm		-
Regulatory reference Article R4412-149 du Code du travail (réf.: INRS ED 6443, 2022; Outil65; Décret n° 2021-1849)  Ethyl acetate (141-78-6)  EU - Indicative Occupational Exposure Limit (IOEL) Local name Ethyl acetate IOEL TWA 734 mg/m³ 200 ppm IOEL STEL 1468 mg/m³ 400 ppm Regulatory reference COMMISSION DIRECTIVE (EU) 2017/164  France - Occupational Exposure Limits Local name Acétate d'éthyle VME (OEL TWA) 734 mg/m³ 200 ppm  VLE (OEL C/STEL) 1468 mg/m³ 400 ppm  VLE (OEL C/STEL) 1468 mg/m³ 400 ppm  Remark Valeurs règlementaires contraignantes Regulatory reference Article R4412-149 du Code du travail (réf.: INRS ED 6443, 2022; Outil65; Décret n° 2019-1487; Décret n° 2020-1546; Décret n° 2021-1349)  n-butyl acetate (123-86-4)  EU - Indicative Occupational Exposure Limit (IOEL) Local name n-Butyl acetate IOEL TWA 241 mg/m³ 50 ppm	Remark	
EU - Indicative Occupational Exposure Limit (IOEL)  Local name    Ethyl acetate	Regulatory reference	Article R4412-149 du Code du travail (réf.: INRS ED 6443, 2022; Outil65; Décret n°
LOCAI name  Ethyl acetate  734 mg/m³ 200 ppm  IOEL STEL  1468 mg/m³ 400 ppm  Regulatory reference  COMMISSION DIRECTIVE (EU) 2017/164  France - Occupational Exposure Limits  Local name  Acétate d'éthyle  VME (OEL TWA)  734 mg/m³ 200 ppm  VLE (OEL C/STEL)  1468 mg/m³ 400 ppm  Remark  Valeurs règlementaires contraignantes  Regulatory reference Article R4412-149 du Code du travail (réf.: INRS ED 6443, 2022; Outil65; Décret n° 2019-1487; Décret n° 2020-1546; Décret n° 2021-434; Décret n° 2021-1849)  n-butyl acetate (123-86-4)  EU - Indicative Occupational Exposure Limit (IOEL)  Local name  n-Butyl acetate  OLL TWA  241 mg/m³ 50 ppm	Ethyl acetate (141-78-6)	
IOEL TWA  734 mg/m³ 200 ppm  IOEL STEL  4468 mg/m³ 400 ppm  Regulatory reference  COMMISSION DIRECTIVE (EU) 2017/164  France - Occupational Exposure Limits  Local name  Acétate d'éthyle  734 mg/m³ 200 ppm  VLE (OEL C/STEL)  1468 mg/m³ 400 ppm  VLE (OEL C/STEL)  1468 mg/m³ 400 ppm  Remark  Valeurs règlementaires contraignantes  Regulatory reference  Article R4412-149 du Code du travail (réf.: INRS ED 6443, 2022; Outil65; Décret n° 2019-1487; Décret n° 2020-1546; Décret n° 2021-434; Décret n° 2021-1849)  n-butyl acetate (123-86-4)  EU - Indicative Occupational Exposure Limit (IOEL)  Local name  n-Butyl acetate  241 mg/m³ 50 ppm	EU - Indicative Occupational Exposure Limit (IOE	L)
IOEL STEL  1468 mg/m³ 400 ppm  Regulatory reference COMMISSION DIRECTIVE (EU) 2017/164  France - Occupational Exposure Limits  Local name Acétate d'éthyle  VME (OEL TWA) 734 mg/m³ 200 ppm  VLE (OEL C/STEL) 1468 mg/m³ 400 ppm  Remark Valeurs règlementaires contraignantes  Regulatory reference Article R4412-149 du Code du travail (réf.: INRS ED 6443, 2022; Outil65; Décret n° 2019-1487; Décret n° 2020-1546; Décret n° 2021-434; Décret n° 2021-1849)  n-butyl acetate (123-86-4)  EU - Indicative Occupational Exposure Limit (IOEL)  Local name  n-Butyl acetate 10EL TWA 241 mg/m³ 50 ppm	Local name	Ethyl acetate
IOEL STEL  1468 mg/m³ 400 ppm  Regulatory reference COMMISSION DIRECTIVE (EU) 2017/164  France - Occupational Exposure Limits  Local name Acétate d'éthyle  VME (OEL TWA) 734 mg/m³ 200 ppm  VLE (OEL C/STEL) 1468 mg/m³ 400 ppm  Remark Valeurs règlementaires contraignantes  Regulatory reference Article R4412-149 du Code du travail (réf.: INRS ED 6443, 2022; Outil65; Décret n° 2019-1487; Décret n° 2020-1546; Décret n° 2021-434; Décret n° 2021-1849)  n-butyl acetate (123-86-4)  EU - Indicative Occupational Exposure Limit (IOEL)  Local name  n-Butyl acetate 10EL TWA 241 mg/m³ 50 ppm	IOEL TWA	734 mg/m³
Regulatory reference COMMISSION DIRECTIVE (EU) 2017/164  France - Occupational Exposure Limits  Local name Acétate d'éthyle  VME (OEL TWA) 734 mg/m³ 200 ppm  VLE (OEL C/STEL) 1468 mg/m³ 400 ppm  Remark Valeurs règlementaires contraignantes  Regulatory reference Article R4412-149 du Code du travail (réf.: INRS ED 6443, 2022; Outil65; Décret n° 2019-1487; Décret n° 2020-1546; Décret n° 2021-434; Décret n° 2021-1849)  n-butyl acetate (123-86-4)  EU - Indicative Occupational Exposure Limit (IOEL)  Local name n-Butyl acetate  IOEL TWA 241 mg/m³ 50 ppm		200 ppm
Regulatory reference  COMMISSION DIRECTIVE (EU) 2017/164  France - Occupational Exposure Limits  Local name  Acétate d'éthyle  VME (OEL TWA)  734 mg/m³  200 ppm  VLE (OEL C/STEL)  4468 mg/m³  400 ppm  Remark  Valeurs règlementaires contraignantes  Regulatory reference  Article R4412-149 du Code du travail (réf.: INRS ED 6443, 2022; Outil65; Décret n° 2019-1487; Décret n° 2020-1546; Décret n° 2021-434; Décret n° 2021-1849)  n-butyl acetate (123-86-4)  EU - Indicative Occupational Exposure Limit (IOEL)  Local name  n-Butyl acetate  IOEL TWA  241 mg/m³  50 ppm	IOEL STEL	1468 mg/m³
France - Occupational Exposure Limits  Local name  Acétate d'éthyle  734 mg/m³ 200 ppm  VLE (OEL C/STEL)  1468 mg/m³ 400 ppm  Remark  Valeurs règlementaires contraignantes  Regulatory reference  Article R4412-149 du Code du travail (réf.: INRS ED 6443, 2022; Outil65; Décret n° 2019-1487; Décret n° 2020-1546; Décret n° 2021-434; Décret n° 2021-1849)  n-butyl acetate (123-86-4)  EU - Indicative Occupational Exposure Limit (IOEL)  Local name  n-Butyl acetate  IOEL TWA  241 mg/m³ 50 ppm		400 ppm
Local name  Acétate d'éthyle  VME (OEL TWA)  734 mg/m³  200 ppm  VLE (OEL C/STEL)  1468 mg/m³  400 ppm  Remark  Valeurs règlementaires contraignantes  Article R4412-149 du Code du travail (réf.: INRS ED 6443, 2022; Outil65; Décret n° 2019-1487; Décret n° 2020-1546; Décret n° 2021-434; Décret n° 2021-1849)  n-butyl acetate (123-86-4)  EU - Indicative Occupational Exposure Limit (IOEL)  Local name  n-Butyl acetate  10EL TWA  241 mg/m³  50 ppm	Regulatory reference	COMMISSION DIRECTIVE (EU) 2017/164
VME (OEL TWA)  734 mg/m³  200 ppm  VLE (OEL C/STEL)  1468 mg/m³  400 ppm  Remark  Valeurs règlementaires contraignantes  Regulatory reference  Article R4412-149 du Code du travail (réf.: INRS ED 6443, 2022; Outil65; Décret n° 2019-1487; Décret n° 2020-1546; Décret n° 2021-434; Décret n° 2021-1849)  n-butyl acetate (123-86-4)  EU - Indicative Occupational Exposure Limit (IOEL)  Local name  n-Butyl acetate  10EL TWA  241 mg/m³  50 ppm	France - Occupational Exposure Limits	
200 ppm  VLE (OEL C/STEL)  1468 mg/m³  400 ppm  Remark  Valeurs règlementaires contraignantes  Regulatory reference  Article R4412-149 du Code du travail (réf.: INRS ED 6443, 2022; Outil65; Décret n° 2019-1487; Décret n° 2020-1546; Décret n° 2021-434; Décret n° 2021-1849)  n-butyl acetate (123-86-4)  EU - Indicative Occupational Exposure Limit (IOEL)  Local name  n-Butyl acetate IOEL TWA  241 mg/m³  50 ppm	Local name	Acétate d'éthyle
VLE (OEL C/STEL)  1468 mg/m³ 400 ppm  Remark  Valeurs règlementaires contraignantes  Regulatory reference  Article R4412-149 du Code du travail (réf.: INRS ED 6443, 2022; Outil65; Décret n° 2019-1487; Décret n° 2020-1546; Décret n° 2021-434; Décret n° 2021-1849)  n-butyl acetate (123-86-4)  EU - Indicative Occupational Exposure Limit (IOEL)  Local name  n-Butyl acetate  10EL TWA  241 mg/m³ 50 ppm	VME (OEL TWA)	734 mg/m³
A00 ppm  Remark  Valeurs règlementaires contraignantes  Regulatory reference  Article R4412-149 du Code du travail (réf.: INRS ED 6443, 2022; Outil65; Décret n° 2019-1487; Décret n° 2020-1546; Décret n° 2021-434; Décret n° 2021-1849)  n-butyl acetate (123-86-4)  EU - Indicative Occupational Exposure Limit (IOEL)  Local name  n-Butyl acetate  10EL TWA  241 mg/m³  50 ppm		200 ppm
Remark  Valeurs règlementaires contraignantes  Regulatory reference  Article R4412-149 du Code du travail (réf.: INRS ED 6443, 2022; Outil65; Décret n° 2019-1487; Décret n° 2020-1546; Décret n° 2021-434; Décret n° 2021-1849)  n-butyl acetate (123-86-4)  EU - Indicative Occupational Exposure Limit (IOEL)  Local name  n-Butyl acetate  10EL TWA  241 mg/m³  50 ppm	VLE (OEL C/STEL)	1468 mg/m³
Regulatory reference  Article R4412-149 du Code du travail (réf.: INRS ED 6443, 2022; Outil65; Décret n° 2019-1487; Décret n° 2020-1546; Décret n° 2021-434; Décret n° 2021-1849)  BU - Indicative Occupational Exposure Limit (IOEL)  Local name  n-Butyl acetate  241 mg/m³  50 ppm		400 ppm
2019-1487; Décret n° 2020-1546; Décret n° 2021-434; Décret n° 2021-1849)  n-butyl acetate (123-86-4)  EU - Indicative Occupational Exposure Limit (IOEL)  Local name  n-Butyl acetate  10EL TWA  241 mg/m³  50 ppm	Remark	Valeurs règlementaires contraignantes
EU - Indicative Occupational Exposure Limit (IOEL)  Local name  IOEL TWA  241 mg/m³  50 ppm	Regulatory reference	
Local name n-Butyl acetate  IOEL TWA 241 mg/m³ 50 ppm	n-butyl acetate (123-86-4)	
10EL TWA 241 mg/m³ 50 ppm	EU - Indicative Occupational Exposure Limit (IOE	L)
50 ppm	Local name	n-Butyl acetate
	IOEL TWA	241 mg/m³
IOEL STEL 723 mg/m³		50 ppm
	IOEL STEL	723 mg/m³

## Safety Data Sheet

n-butyl acetate (123-86-4)	
	150 ppm
Regulatory reference	COMMISSION DIRECTIVE (EU) 2019/1831
France - Occupational Exposure Limits	
Local name	Acétate de n-butyle
VME (OEL TWA)	241 mg/m³
	50 ppm
VLE (OEL C/STEL)	723 mg/m <sup>3</sup>
	150 ppm
Remark	Valeurs règlementaires contraignantes
Regulatory reference	Article R4412-149 du Code du travail (réf.: INRS ED 6443, 2022; Outil65; Décret n° 2021-1849)
isopentyl acetate (123-92-2)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	Isopentylacetate
IOEL TWA	270 mg/m³
	50 ppm
IOEL STEL	540 mg/m³
	100 ppm
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC
France - Occupational Exposure Limits	
Local name	Acétate d'isopentyle
VME (OEL TWA)	270 mg/m³
	50 ppm
VLE (OEL C/STEL)	540 mg/m³
	100 ppm
Remark	Valeurs règlementaires contraignantes
Regulatory reference	Article R4412-149 du Code du travail (réf.: INRS ED 6443, 2022; Outil65; Décret n° 2019-1487; Décret n° 2020-1546; Décret n° 2021-434; Décret n° 2021-1849)
ethanol/ ethyl alcohol (64-17-5)	
France - Occupational Exposure Limits	
Local name	Alcool éthylique
VME (OEL TWA)	1900 mg/m³
	1000 ppm
VLE (OEL C/STEL)	9500 mg/m³
	5000 ppm
Remark	Valeurs recommandées/admises
Regulatory reference	Circulaire du Ministère du travail (réf.: INRS ED 6443, 2022; Outil65)

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006

#### 8.2. Exposure controls

#### **Appropriate engineering controls**

#### Appropriate engineering controls:

Ensure good ventilation of the work station.

#### Personal protection equipment

#### Personal protective equipment:

Wear recommended personal protective equipment.

#### Personal protective equipment symbol(s):







#### Eye and face protection

#### Eye protection:

Safety glasses

#### Skin protection

#### Skin and body protection:

Wear suitable protective clothing

#### Hand protection:

Protective gloves

Physical state

**Boiling point** 

#### **Respiratory protection**

#### Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

#### **Environmental exposure controls**

## **Environmental exposure controls:**

Avoid release to the environment.

#### **SECTION 9: Physical and chemical properties**

#### 9.1. Information on basic physical and chemical properties

Colour : brown.

Odour : Characteristic.

Odour threshold : Not available

Melting point : Not applicable

Freezing point : Not available

Flammability : Highly flammable liquid and vapour.

: Liquid

: > 35 °C

pH : 4(3-5)Viscosity, kinematic : Not available Solubility : soluble in water.

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006

Partition coefficient n-octanol/water (Log Kow) : Not available

Vapour pressure : Not available

Vapour pressure at 50°C : Not available

Density : Not available

Relative density : 1,15 (1,13 – 1,18)

Relative vapour density at 20°C : Not available

Particle characteristics : Not applicable

#### 9.2. Other information

No additional information available

## **SECTION 10: Stability and reactivity**

#### 10.1. Reactivity

Highly flammable liquid and vapour.

#### 10.2. Chemical stability

Stable under normal conditions.

#### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

#### 10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

#### 10.5. Incompatible materials

No additional information available

#### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## **SECTION 11: Toxicological information**

## 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Not classified (Based on available data, the classification criteria are not met)

Acute toxicity (dermal) : Not classified (Based on available data, the classification criteria are not met)

Acute toxicity (inhalation) : Not classified (Based on available data, the classification criteria are not met)

Acetic acid (64-19-7)		
LD50 oral rat	3310 mg/kg bodyweight Animal: rat	
LD50 oral	4960 mg/kg bodyweight Animal: mouse	
LD50 dermal rabbit	1060 mg/kg Source: HSDB, NITE	
LC50 Inhalation - Rat [ppm]	16000 ppm Source: ChemIDPlus	
Isoamyl alcohol (123-51-3)		
LD50 oral rat	> 5000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)	
LD50 dermal rabbit	≈ 3216 mg/kg bodyweight Animal: rabbit, Animal sex: male, 95% CL: 2373 - 4350	
LC50 Inhalation - Rat (Vapours)	10 mg/l Source: ECHA	
Ethyl acetate (141-78-6)		
LD50 oral rat	11,3 ml/kg Source: ECHA	
LD50 oral	4934 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 401 (Acute Oral Toxicity)	
LD50 dermal rabbit	> 20000 mg/kg bodyweight Animal: rabbit, Animal sex: male	
n-butyl acetate (123-86-4)		
LD50 oral rat	3200 ml/kg Source: ECHA	

04/03/2025 (Revision date) EN (English) 8/18

## Safety Data Sheet

n-butyl acetate (123-86-4)	
LD50 dermal rabbit	> 17600 mg/kg Source: ECHA
LC50 Inhalation - Rat (Vapours)	1802 mg/l Source: ECHA
isopentyl acetate (123-92-2)	
LD50 dermal rabbit	> 5000 mg/kg bodyweight Animal: rabbit
ethanol/ ethyl alcohol (64-17-5)	
LD50 oral rat	15010 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 401 (Acute Oral Toxicity), 95% CL: 14450 - 15560
LD50 oral	8300 mg/kg bodyweight Animal: mouse
Skin corrosion/irritation	: Not classified (Based on available data, the classification criteria are not met)
	pH: 4 (3 – 5)
Acetic acid (64-19-7)	
рН	2,4 Source: ECHA
n-butyl acetate (123-86-4)	
рН	6,2 Temp.: 20 °C Concentration: (≈)5 g/L
Serious eye damage/irritation	: Causes serious eye irritation.
	pH: 4 (3 – 5)
Acetic acid (64-19-7)	
рН	2,4 Source: ECHA
n-butyl acetate (123-86-4)	
рН	6,2 Temp.: 20 °C Concentration: (≈)5 g/L
Respiratory or skin sensitisation	: Not classified (Based on available data, the classification criteria are not met)
Germ cell mutagenicity	: Not classified (Based on available data, the classification criteria are not met)
Carcinogenicity	: Not classified (Based on available data, the classification criteria are not met)
ethanol/ ethyl alcohol (64-17-5)	
IARC group	1 - Carcinogenic to humans
Reproductive toxicity	: Not classified (Based on available data, the classification criteria are not met)
STOT-single exposure	: Not classified (Based on available data, the classification criteria are not met)
Isoamyl alcohol (123-51-3)	
STOT-single exposure	May cause respiratory irritation.
Ethyl acetate (141-78-6)	
STOT-single exposure	May cause drowsiness or dizziness.
n-butyl acetate (123-86-4)	
STOT-single exposure	May cause drowsiness or dizziness.
STOT-repeated exposure	: Not classified (Based on available data, the classification criteria are not met)
Acetic acid (64-19-7)	
NOAEL (oral, rat, 90 days)	290 mg/kg bodyweight Animal: rat, Animal sex: male
Isoamyl alcohol (123-51-3)	
NOAEL (oral, rat, 90 days)	1250 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006

Ethyl acetate (141-78-6)	
LOAEL (oral, rat, 90 days)	3600 mg/kg bodyweight Animal: rat, Guideline: EPA OTS 795.2600 (Subchronic Oral Toxicity Test)
NOAEL (oral, rat, 90 days)	900 mg/kg bodyweight Animal: rat, Guideline: EPA OTS 795.2600 (Subchronic Oral Toxicity Test)
isopentyl acetate (123-92-2)	
NOAEL (subchronic, oral, animal/female, 90 days)	443,07 mg/kg bodyweight Animal: , Animal sex: female
ethanol/ ethyl alcohol (64-17-5)	
LOAEL (oral, rat, 90 days)	3200 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)
NOAEL (oral, rat, 90 days)	1730 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents), Remarks on results: other:
NOAEL (subchronic, oral, animal/male, 90 days)	< 9700 mg/kg bodyweight Animal: mouse, Animal sex: male, Guideline: EPA OPPTS 870.3100 (90-Day Oral Toxicity in Rodents)
NOAEL (subchronic, oral, animal/female, 90 days)	> 9400 mg/kg bodyweight Animal: mouse, Animal sex: female, Guideline: EPA OPPTS 870.3100 (90-Day Oral Toxicity in Rodents)
Aspiration hazard	Not classified (Based on available data, the classification criteria are not met)
Acetic acid (64-19-7)	
Viscosity, kinematic	1,015 mm²/s
Isoamyl alcohol (123-51-3)	
Viscosity, kinematic	5,32 mm²/s Temp.: '20°C' Parameter: 'kinematic viscosity (in mm²/s)'
n-butyl acetate (123-86-4)	
Viscosity, kinematic	0,83 mm²/s Temp.: '20°C' Parameter: 'kinematic viscosity (in mm²/s)'
isopentyl acetate (123-92-2)	
Viscosity, kinematic	1,176 mm²/s
ethanol/ ethyl alcohol (64-17-5)	
Viscosity, kinematic	1,488 mm²/s
11.2 Information on other becoude	

## 11.2. Information on other hazards

No additional information available

SECTION 12: Ecological information
------------------------------------

12.1. Toxicity	
Ecology - general	: The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.
Hazardous to the aquatic environment, short–term (acute)	: Not classified (Based on available data, the classification criteria are not met)
Hazardous to the aquatic environment, long-term (chronic)	: Not classified (Based on available data, the classification criteria are not met)

Acetic acid (64-19-7)	
LC50 - Fish [1]	> 1000 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)
LC50 - Fish [2]	> 300,82 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)
EC50 - Crustacea [1]	> 1000 mg/l Test organisms (species): Daphnia magna

## Safety Data Sheet

Acetic acid (64-19-7)	
EC50 - Crustacea [2]	> 300,82 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	> 1000 mg/l Test organisms (species): Skeletonema costatum
EC50 72h - Algae [2]	> 300,82 mg/l Test organisms (species): Skeletonema costatum
Isoamyl alcohol (123-51-3)	
LC50 - Fish [1]	700 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)
EC50 - Crustacea [1]	255 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	> 500 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)
EC50 72h - Algae [2]	493 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)
EC50 96h - Algae [1]	274 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)
EC50 96h - Algae [2]	181 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)
Ethyl acetate (141-78-6)	
LC50 - Fish [1]	230 mg/l Test organisms (species): Pimephales promelas
NOEC (chronic)	2,4 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
n-butyl acetate (123-86-4)	
LC50 - Fish [1]	18 mg/l Test organisms (species): Pimephales promelas
EC50 - Crustacea [1]	44 mg/l Test organisms (species): Daphnia sp.
EC50 - Other aquatic organisms [1]	32 mg/l Test organisms (species): Artemia salina
EC50 72h - Algae [1]	674,7 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)
NOEC (chronic)	23 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
isopentyl acetate (123-92-2)	
LC50 - Fish [1]	22 – 46 mg/l Test organisms (species): Danio rerio (previous name: Brachydanio rerio)
EC50 - Crustacea [1]	42 mg/l Test organisms (species): other:Daphnia magna STRAUS
ethanol/ ethyl alcohol (64-17-5)	
LC50 - Fish [1]	14,2 g/I Test organisms (species): Pimephales promelas
EC50 - Crustacea [1]	> 10000 mg/l Test organisms (species): Daphnia magna
EC50 96h - Algae [1]	≈ 22000 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
ErC50 algae	275 mg/l Source: ECHA
NOEC (chronic)	9,6 mg/l Test organisms (species): Daphnia magna Duration: '9 d'
12.2. Persistence and degradability	
ORGANIC APPLE FLAVOUR PO-0509	
Persistence and degradability	Not rapidly degradable
Acetic acid (64-19-7)	
Persistence and degradability	Not rapidly degradable

### Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006

Isoamyl alcohol (123-51-3)	
Persistence and degradability	Not rapidly degradable
Ethyl acetate (141-78-6)	
Persistence and degradability	Not rapidly degradable
n-butyl acetate (123-86-4)	
Persistence and degradability	Not rapidly degradable
isopentyl acetate (123-92-2)	
Persistence and degradability	Not rapidly degradable
ethanol/ ethyl alcohol (64-17-5)	
Persistence and degradability	Not rapidly degradable
12.3. Bioaccumulative potential	
Acetic acid (64-19-7)	
Partition coefficient n-octanol/water (Log Pow)	-0,17 Source: ECHA
Isoamyl alcohol (123-51-3)	
Partition coefficient n-octanol/water (Log Pow)	1,16 Source: HSDB
Ethyl acetate (141-78-6)	
Partition coefficient n-octanol/water (Log Pow)	0,73 Source: ICSC
n-butyl acetate (123-86-4)	
Partition coefficient n-octanol/water (Log Pow)	1,78 Source: HSDB
isopentyl acetate (123-92-2)	
Partition coefficient n-octanol/water (Log Pow)	2,13 Source: ICSC
ethanol/ ethyl alcohol (64-17-5)	
Partition coefficient n-octanol/water (Log Pow)	-0,32 Source: ICSC
12.4. Mobility in soil	
No additional information available	

No additional information available

#### 12.5. Results of PBT and vPvB assessment

No additional information available

#### 12.6. Endocrine disrupting properties

No additional information available

## 12.7. Other adverse effects

No additional information available

### **SECTION 13: Disposal considerations**

#### 13.1. Waste treatment methods

: Disposal must be done according to official regulations. Regional waste regulation

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting

instructions.

Sewage disposal recommendations : Disposal must be done according to official regulations.

Product/Packaging disposal recommendations : Disposal must be done according to official regulations.

Additional information : Flammable vapours may accumulate in the container. Do not re-use empty containers.

### **SECTION 14: Transport information**

In accordance with ADR / IMDG / IATA

12/18 04/03/2025 (Revision date) EN (English)

### Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006

ADR	IMDG	IATA
14.1. UN number or ID number		
UN 1197	UN 1197	UN 1197
14.2. UN proper shipping name		
EXTRACTS, LIQUID	EXTRACTS, LIQUID	Extracts, liquid
Transport document description		
UN 1197 EXTRACTS, LIQUID, 3, II, (D/E)	UN 1197 EXTRACTS, LIQUID, 3, II	UN 1197 Extracts, liquid, 3, II
14.3. Transport hazard class(es)		
3	3	3
3	3	
14.4. Packing group		
II	II	II
14.5. Environmental hazards		
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No EmS-No. (Fire): F-E EmS-No. (Spillage): S-D	Dangerous for the environment: No
No supplementary information available		

#### 14.6. Special precautions for user

### **Overland transport**

Classification code (ADR) : F1

Special provisions (ADR) : 601, 640C

Limited quantities (ADR) : 5I

Excepted quantities (ADR) : E2

Packing instructions (ADR) : P001

Mixed packing provisions (ADR) : MP19

Portable tank and bulk container instructions : T4

(ADR)

Portable tank and bulk container special : TP1, TP8

provisions (ADR)

Tank code (ADR) : L1.5BN

Vehicle for tank carriage : FL

Transport category (ADR) : 2

Special provisions for carriage - Operation (ADR) : S2, S20

Hazard identification number (Kemler No.) : 33

Hazard identification number (Kemler No.) : 33
Orange plates :

33 1197

Tunnel restriction code (ADR) : D/E EAC code : 3YE

Transport by sea

Limited quantities (IMDG) : 5 L

#### Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006

Excepted quantities (IMDG) : E2

Packing instructions (IMDG) : P001

IBC packing instructions (IMDG) : IBC02

Tank instructions (IMDG) : T4

Tank special provisions (IMDG) : TP1, TP8

Stowage category (IMDG) : B

Properties and observations (IMDG) : Usually consist of alcoholic solutions. Miscibility with water depends upon the

composition.

#### Air transport

PCA Excepted quantities (IATA) : E2 PCA Limited quantities (IATA) : Y341 PCA limited quantity max net quantity (IATA) : 1L PCA packing instructions (IATA) : 353 PCA max net quantity (IATA) : 5L CAO packing instructions (IATA) : 364 CAO max net quantity (IATA) : 60L Special provisions (IATA) : A3 ERG code (IATA) : 3L

#### 14.7. Maritime transport in bulk according to IMO instruments

Not applicable

#### **SECTION 15: Regulatory information**

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### **EU-Regulations**

#### **REACH Annex XVII (Restriction List)**

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

#### **REACH Annex XIV (Authorisation List)**

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

#### **REACH Candidate List (SVHC)**

Contains no substance(s) listed on the REACH Candidate List

#### **PIC Regulation (Prior Informed Consent)**

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

#### **POP Regulation (Persistent Organic Pollutants)**

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

#### Ozone Regulation (2024/590)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 2024/590 on substances that deplete the ozone layer)

#### Council Regulation (EC) for the control of dual-use items

Contains no substance subject to the COUNCIL REGULATION (EC) for the control of dual-use items

#### **Explosives Precursors Regulation (2019/1148)**

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

#### Drug Precursors Regulation (273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006

#### **National regulations**

#### France

Occupational diseases	
Code	Description
RG 84	Conditions caused by liquid organic solvents for professional use: saturated or unsaturated aliphatic or cyclic liquid hydrocarbons and mixtures thereof; liquid halogenated hydrocarbons; nitrated derivatives of aliphatic hydrocarbons; alcohols; glycols, glycol ethers; ketones; aldehydes; aliphatic and cyclic ethers, including tetrahydrofuran; esters; dimethylformamide and dimethylacetamine; acetonitrile and propionitrile; pyridine; dimethylsulfone and dimethylsulfoxide

#### Germany

VOC ordinance (ChemVOCFarbV) :

Water hazard class (WGK) : WGK 3, Highly hazardous to water (Classification according to AwSV, Annex 1).

Major Accidents Ordinance (12. BlmSchV) : Is not subject to the Major Accidents Ordinance (12. BlmSchV)

Netherlands

SZW-lijst van kankerverwekkende stoffen : Ethanol/ Ethyl alcohol is listed SZW-lijst van mutagene stoffen : None of the components are listed SZW-lijst van reprotoxische stoffen - : Ethanol/ Ethyl alcohol is listed

SZW-lijst van reprotoxische stoffen –

Vruchtbaarheid

SZW-lijst van reprotoxische stoffen – : Ethanol/ Ethyl alcohol is listed

Ontwikkeling

Borstvoeding

Denmark

Class for fire hazard : Class I-1
Store unit : 1 liter

Classification remarks : F <Flam. Liq. 2>; Emergency management guidelines for the storage of flammable

: Ethanol/ Ethyl alcohol is listed

liquids must be followed

Danish National Regulations : Pregnant/breastfeeding women working with the product must not be in direct contact

with the product

#### Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006

#### **Poland**

**Polish National Regulations** 

: Act of 25 February 2011 on chemical substances and their mixtures (J. o L. No. 63, item 322 as amended; consolidated text J. o L. 2019, item 1225).

Act of 14 December 2012 on waste (J. o L. 2013, item 322 as amended; consolidated text J. o L. 2020, item 797).

The announcement of Marshal of the Sejm of the Republic of Poland dated 19 October 2016 concerning the consolidated text announcement of the decree on the management of packaging and packaging waste (J. o L. 2016, item 1863 as amended). Decree of the Minister of Environment of 14 December 2014 on the catalogue of waste (J. o L. 2014, item 1923).

Act of 19 August 2011 on the Carriage of Dangerous Goods (J. o L. 2011 No. 227, item 1367 as amended; consolidated text J. o L. 2020, item 154).

Regulation of the Minister of Family, Labour and Social Policy of 12 June 2018 on the highest permissible concentration and intensity of noxious agents for health at work environment (J. o L. item 1286 as amended).

The announcement of Minister of Health dated 9 September 2016 concerning the consolidated text announcement of the decree of the Minister of Health of 30 December 2004 on health and safety at work related to exposure to chemical agents at work (J. o L. of 16 September 2016, item 1488)

Regulation of the Minister of Health of 2 February 2011 on tests and measurements of the noxious agents for health at work environment (J. o L. No. 33, item 166 as amended).

Regulation of the Minister of Environment of 9 December 2003 on particularly hazardous substances to the environment (J. o L. No. 217, item 2141). ADR Agreement: Government Statement of 13 March 2023 on the entry into force of amendments to Annexes A and B to the Agreement concerning the International Carriage of Dangerous Goods by Road (ADR), signed in Geneva on 30 September 1957 (J. o. L. 2023, item 891)

#### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information	
Abbreviations and acronyms:	
ACGIH	American Conference of Government Industrial Hygienists
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BLV	Biological limit value
BOD	Biochemical oxygen demand (BOD)
CAS-No.	Chemical Abstract Service number
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
COD	Chemical oxygen demand (COD)
CSA	Chemical safety assessment
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC-No.	European Community number
EC50	Median effective concentration
ED	Endocrine disruptor
EN	European Standard

## Safety Data Sheet

Abbreviations and acro	onyms:
EWC	European waste catalogue
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
Log Kow	Partition coefficient n-octanol/water (Log Kow)
Log Pow	Partition coefficient n-octanol/water (Log Pow)
MAK	maximum workplace concentration
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
N.O.S.	Not Otherwise Specified
OECD	Organisation for Economic Co-operation and Development
OEL	Occupational Exposure Limit
OSHA	Occupational Safety Health Administration
РВТ	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
PPE	Personal protection equipment
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
STP	Sewage treatment plant
TF	Technical function
ThOD	Theoretical oxygen demand (ThOD)
TLM	Median Tolerance Limit
TWA	Time Weighted Average
VOC	Volatile Organic Compounds
vPvB	Very Persistent and Very Bioaccumulative
UFI	Unique Formula Identifier

Full text of H- and EUH-statements:	
Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
Skin Corr. 1A	Skin corrosion/irritation, Category 1, Sub-Category 1A

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006

Full text of H- and EUH-statements:	
Skin Corr. 1B	Skin corrosion/irritation, Category 1, Sub-Category 1B
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Respiratory tract irritation
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H318	Causes serious eye damage.
Н319	Causes serious eye irritation.
Н332	Harmful if inhaled.
H335	May cause respiratory irritation.
Н336	May cause drowsiness or dizziness.
EUH066	Repeated exposure may cause skin dryness or cracking.

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.