

Sarda Bio Polymers Private Limited

CIN: U24233MH2012PTC234791 GSTIN: 08AARCS9529A1ZZ

Registered Office: 2nd Floor, 14/16, Gopal Das Mantri Marg, Vithalwadi, Kalbadevi Road, Mumbai, India – 400 002

Factory: H1-105 to 108, 4th Phase Industrial Area, Pali-Marwar, Rajasthan, India – 306 401

Email: support@sardabiopolymers.com | Website: www.sardabiopolymers.com

MATERIAL SAFETY DATA SHEET

1.0 Chemical Product and Company Identification

Product name: Psyllium Husk Powder
Manufacturer: Sarda Bio Polymers Pvt. Ltd

Chemical Family: Dietry Fibre Date issued: 1st April, 2021

2.0 Composition/Information on Ingredients

COMPONENT CAS NO: Psyllium Husk

H.S.Code: 12119032

3.0 Hazards Identification

Emergency Overview:

Appearance and Odor: white to cream colored powder

With natural odor

Potential Health Effects

LIKELY ROUTES OF EXPOSURE: Skin contact and inhalation

EYE CONTACT: No more than slightly irritating based on studies. The dry powder may cause foreign body irritation in some individuals.

SKIN CONTACT: No more than slightly irritating of gumminess based on studies.

INHALATION: Inhalation of the dust may cause coughing and sneezing

INGESTION: Is not toxic if swallowed based on toxicity studies. No significant adverse health effects are expected to develop if only small amounts(less than a mouthful) are swallowed

Refer to Section 11 for toxicological information:

4.0 First aid Measures:

IF IN EYES OR SKIN, immediate first aid is not likely to be required. However, this material can be removed with water. Wash heavily contaminated clothing before reuse

IF INHALED, immediate first aid is not likely to be required. However, if symptoms occur, remove to fresh air. Remove material from eyes, skin and clothing.

IF SWALLOWED, immediate first aid is not likely to be required. A physician or Poison Control Center can be contacted for advice. Wash heavily contaminated clothing before reuse.

5.0 Fire Fighting Measures:

FLASH POINT: Not applicable

HAZARDOUS PRODUCTS OF COMBUSTION: carbon dioxide, carbon monoxide



EXTINGUISHING MEDIA: In case of fire, use water, dry chemical, CO₂, or alcohol foam

UNUSUAL FIRE AND EXPLOSION HAZARDS: No self explosion risk.

FIRE FIGHTING EQUIPMENT: Fire fighters and others exposed to products of combustion should wear self-contained breathing apparatus. Equipment should be thoroughly de-contaminated after use.

6.0 Accidental Release Measure:

In case of spill, do not blow material. Use vacuum equipment.

NOTE- The use of water wash down is not recommended unless the spilled material is already wet. Wet material on a walking surface will be extremely slippery. We spills should be thoroughly flushed with water until non-slippery.

Refer to Section 13 for disposal information and Section 15 for reportable quantity information.

7.0 Handing and Storage:

HANDLE IN ACCORDANCE WITH GOOD INDUSTRIAL HYGIENE AND SAFETY

PRACTICES.THESE PRACTICES INCLUDE AVOIDING UNNECESSARY EXPOSURE AND REMOVAL OF MATERIAL FROM EYES, SKIN AND CLOTHING.

Keep away from heat, sparks and flame. Avoid creating dust cloud in handling transfer and clean up.

8.0 Exposure controls/personal protection:

EYE PROTECTION: This product does not cause significant eye irritation or eye toxicity requiring special protection. Use good industrial practice to avoid eye contact.

SKIN PROTECTION: Although this product does not present a significant skin concern, minimize skin contamination by following good industrial practice. Wearing protective gloves is recommended. Wash hands and contaminated skin thoroughly after handling.

RESPIRATORY PROTECTION: Avoid breathing dust. Use appropriate approved respiratory protection equipment when airborne exposure limits are exceeded(see below). Consult the respirator manufacturer to determine appropriate type equipment for a given application.

VENTILATION: Provide natural or mechanical ventilation to control exposure levels below airborne exposure limits (see below). The use of local mechanical exhaust ventilation is preferred at sources of air contamination such as open process equipment.

AIRBORNE EXPOSURE LIMITS: Not established specific exposure limits for particulates.

9.0 Physical and Chemical Properties

Molecular Weight: approximately 1,000,000

Appearance: Creamy white powder Odor: slight natural bean odor

PH: approximately neutral (as a 1% solution) Bulk Density: approximately 50lb/cu.ft.

Solubility in Water: soluble, forming viscous solutions, becoming a paste at concentrations greater than about

5%

NOTE: These physical data are typical values based on material tested but many vary from sample to sample. Typical values should not be construed as a guaranteed analysis of any specific lot or as specifications for the product.



10.0 Stability and Reactivity

STABILITY: Product is stable under normal conditions of storage and handling. Store in a cool and dry place to maintain product performance.

MATERIALS TO AVOID: strong oxidizers

HAZARDOUS DECOMPOSITION PRODUCTS: Thermal decomposition products may include carbon dioxide and carbon monoxide.

HAZARDOUS POLYMERIZATION: will not occur

11.0 Toxicological Information

The dry powder may cause foreign body irritation in some individuals. Prolonged contact with the dry powder may cause drying or chapping of the skin. Excessive inhalation of dust may be annoying and can mechanically impede respiration.

12.0 Ecological information

The following data have been classified using the criteria adopted by the European Economic Community (EEC) for aquatic organism toxicity. A legend summarizing the classification scheme appearance below.

48hr.LC50; Daphnia magna: 980mg/L; practically nontoxic >500,000ppm suspended particulate phase.

Legend for Aquatic Organism Toxicity (Journal of the European Communities, Annex VII A, Section 5.2.1)

Values Classifications LC50 or EC50 >1.0mg/L Toxic LC50 or EC50 >10mg/L Harmful

LC50 or EC50 >100mg/L Practically Nontoxic

BOD5 is approximately 200mg O2/gram.COD is approximately 1600mg O2/g.

13.0 Disposal Considerations

Dispose of in accordance with local, state and federal regulations. Dry or wet solid material can be land filled in accordance with local, state and federal regulations. Liquids may be severed in accordance with local, state and federal regulations if care is taken to avoid plugage or blockage of sewer systems recognizing that these materials are intended to increase viscosity and form gels. As a carbohydrate, this material should be readily biodegradable.

14.0 Transport Information

This product is not hazardous under the applicable DOT, ICAO/IATA, or IMDG regulations

Pls apply the appropriate regulations to properly classify your shipment for transportation.

15.0 Regulatory Information

The ingredients of this product are on the TSCA Chemical Substances Inventory, the Canadian Domestic Substances List, and are included in the European Inventory of Existing Commercial Chemical Substances (EINECS)

SARA HAZARD NOTIFICATION

Hazard Categories Under Title III Rules (40 CFR 370): not applicable



Section 302 Extremely Hazardous Substances: not applicable Section 313 Toxic Chemical(s): not applicable

CERCLA REPORTABLE QUANTITY: not applicable

16.0 Other Information

Health Fire Reactivity

NFPA Rating: 0 0 0 HMIS Rating: 0 0 0
