ORGANIC MANGO FLAVOUR MA-0449

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006
Issue date: 5/14/2021 Revision date: 11/13/2026 Supersedes version of: 5/9/2023 Version: 1.2

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name : ORGANIC MANGO FLAVOUR MA-0449
UFI : VV82-QS5R-Y309-TXG6
Product code : MANG-MA0449

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

Main use category : Industrial use,Professional use

1.3. Details of the supplier of the safety data sheet

SELECTAROME SAS
45 Bd Marcel Pagnol
PA Aromagrasse
FR 06130 GRASSE
France
T +33 4.93.36.22.22, F 04.93.40.71.72
reglementaire@selectarome.com

1.4. Emergency telephone number

Country/Area	Organisation	Emergency number
France	ORFILA.	+33 1 45 42 59 59

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flammable liquids, Category 3 H226
Serious eye damage/eye irritation, Category 2 H319
Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

Flammable liquid and vapour. Causes serious eye irritation.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS02 GHS07

Signal word (CLP) : Warning
Hazard statements (CLP) : H226 - Flammable liquid and vapour.
H319 - Causes serious eye irritation.
Precautionary statements (CLP) : P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P280 - Wear protective gloves, protective clothing, eye protection.
P337+P313 - If eye irritation persists: Get medical advice/attention.

2.3. Other hazards

Contains no PBT and/or vPvB substances ≥ 0.1% assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
ethanol/ ethyl alcohol substance with national workplace exposure limit(s) (FR)	CAS-No.: 64-17-5 EC-No.: 200-578-6 EC Index-No.: 603-002-00-5	15 - 20	Flam. Liq. 2, H225 Eye Irrit. 2, H319
Acetic acid substance with national workplace exposure limit(s) (FR); substance with a Community workplace exposure limit	CAS-No.: 64-19-7 EC-No.: 200-580-7 EC Index-No.: 607-002-00-6	< 0.1	Flam. Liq. 3, H226 Skin Corr. 1A, H314 Eye Dam. 1, H318
n-butyl acetate substance with national workplace exposure limit(s) (FR); substance with a Community workplace exposure limit	CAS-No.: 123-86-4 EC-No.: 204-658-1 EC Index-No.: 607-025-00-1	< 0.1	Flam. Liq. 3, H226 STOT SE 3, H336 EUH066
ethyl acetate substance with national workplace exposure limit(s) (FR); substance with a Community workplace exposure limit	CAS-No.: 141-78-6 EC-No.: 205-500-4 EC Index-No.: 607-022-00-5	< 0.1	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
Isoamyl acetate / Isopentyl acetate substance with national workplace exposure limit(s) (FR); substance with a Community workplace exposure limit	CAS-No.: 123-92-2 EC-No.: 204-662-3 EC Index-No.: 607-130-00-2 REACH-no: 01-2119548408-32	< 0.1	Flam. Liq. 3, H226
butan-1-ol; n-butanol substance with national workplace exposure limit(s) (FR)	CAS-No.: 71-36-3 EC-No.: 200-751-6 EC Index-No.: 603-004-00-6	< 0.1	Flam. Liq. 3, H226 Acute Tox. 4 (Oral), H302 (ATE=500 mg/kg bodyweight) STOT SE 3, H335 Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H336
Isoamyl alcohol substance with national workplace exposure limit(s) (FR); substance with a Community workplace exposure limit	CAS-No.: 123-51-3 EC-No.: 204-633-5	< 0.1	Flam. Liq. 3, H226 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H335 Aquatic Chronic 3, H412 EUH066
Propionic acid substance with national workplace exposure limit(s) (FR); substance with a Community workplace exposure limit	CAS-No.: 79-09-4 EC-No.: 201-176-3 EC Index-No.: 607-089-00-0	< 0.1	Flam. Liq. 3, H226 Skin Corr. 1B, H314 Eye Dam. 1, H318 STOT SE 3, H335

Specific concentration limits:		
Name	**Product identifier**	**Specific concentration limits (%)**
Acetic acid	CAS-No.: 64-19-7 EC-No.: 200-580-7 EC Index-No.: 607-002-00-6	(10 ≤ C < 25) Skin Irrit. 2; H315 (10 ≤ C < 25) Eye Irrit. 2; H319 (25 ≤ C < 90) Skin Corr. 1B; H314 (90 ≤ C ≤ 100) Skin Corr. 1A; H314
Propionic acid	CAS-No.: 79-09-4 EC-No.: 201-176-3 EC Index-No.: 607-089-00-0	(10 ≤ C < 25) Skin Irrit. 2; H315 (10 ≤ C < 25) Eye Irrit. 2; H319 (10 ≤ C ≤ 100) STOT SE 3; H335 (25 ≤ C ≤ 100) Skin Corr. 1B; H314

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.

First-aid measures after skin contact : Rinse skin with water/shower. Take off immediately all contaminated clothing.

First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

First-aid measures after ingestion : Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after eye contact : Eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Flammable liquid and vapour.

Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Advice for firefighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid contact with skin and eyes.

For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.

Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapours may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Avoid contact with skin and eyes.

Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Ground/bond container and receiving equipment.

Storage conditions : Store in a well-ventilated place. Keep cool. Keep container tightly closed.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

National occupational exposure and biological limit values

Isoamyl alcohol (123-51-3)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	Isoamyl alcohol
IOEL TWA	18 mg/m³
	5 ppm
IOEL STEL	37 mg/m³
	10 ppm
Regulatory reference	COMMISSION DIRECTIVE (EU) 2019/1831

Acetic acid (64-19-7)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	Acetic acid
IOEL TWA	25 mg/m³
	10 ppm
IOEL STEL	50 mg/m³
	20 ppm
Regulatory reference	COMMISSION DIRECTIVE (EU) 2017/164

Propionic acid (79-09-4)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	Propionic acid
IOEL TWA	31 mg/m³
	10 ppm
IOEL STEL	62 mg/m³
	20 ppm
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC

n-butyl acetate (123-86-4)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	n-Butyl acetate
IOEL TWA	241 mg/m³
	50 ppm
IOEL STEL	723 mg/m³
	150 ppm
Regulatory reference	COMMISSION DIRECTIVE (EU) 2019/1831

ethyl acetate (141-78-6)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	Ethyl acetate
IOEL TWA	734 mg/m³
	200 ppm
IOEL STEL	1468 mg/m³
	400 ppm
Regulatory reference	COMMISSION DIRECTIVE (EU) 2017/164

Isoamyl acetate / Isopentyl acetate (123-92-2)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	Isopentylacetate
IOEL TWA	270 mg/m³
	50 ppm
IOEL STEL	540 mg/m³

Isoamyl acetate / Isopentyl acetate (123-92-2)	
	100 ppm
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC

8.2. Exposure controls

Appropriate engineering controls

Appropriate engineering controls:
Ensure good ventilation of the work station.

Personal protection equipment

Personal protective equipment symbol(s):



Eye and face protection

Eye protection:
Safety glasses

Skin protection

Skin and body protection:
Wear suitable protective clothing

Hand protection:
Protective gloves

Respiratory protection

Respiratory protection:
In case of insufficient ventilation, wear suitable respiratory equipment

Environmental exposure controls

Environmental exposure controls:
Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	:	Liquid
Colour	:	brown.
Odour	:	Characteristic.
Odour threshold	:	Not available
Melting point	:	Not applicable
Freezing point	:	Not available
Boiling point	:	Not available
Flammability	:	Not applicable
Lower explosion limit	:	Not available
Upper explosion limit	:	Not available
Flash point	:	23 °C
Auto-ignition temperature	:	Not available
Decomposition temperature	:	Not available
pH	:	3.6 (2.6 – 4.6)
Viscosity, kinematic	:	Not available
Solubility	:	soluble in water.
Partition coefficient n-octanol/water (Log Kow)	:	Not available
Vapour pressure	:	Not available
Vapour pressure at 50°C	:	Not available

Density	:	Not available
Relative density	:	1.22 (1.2 – 1.24)
Relative vapour density at 20°C	:	Not available
Particle characteristics	:	Not applicable

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Flammable liquid and vapour.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral)	:	Not classified (Based on available data, the classification criteria are not met)
Acute toxicity (dermal)	:	Not classified (Based on available data, the classification criteria are not met)
Acute toxicity (inhalation)	:	Not classified (Based on available data, the classification criteria are not met)

butan-1-ol; n-butanol (71-36-3)	
LD50 oral rat	≈ 2292 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
LD50 dermal rabbit	≈ 3430 mg/kg bodyweight Animal: rabbit, Animal sex: male, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)

ethanol/ ethyl alcohol (64-17-5)	
LD50 oral rat	15010 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 401 (Acute Oral Toxicity), 95% CL: 14450 - 15560
LD50 oral	8300 mg/kg bodyweight Animal: mouse

Isoamyl alcohol (123-51-3)	
LD50 oral rat	> 5000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
LD50 dermal rabbit	≈ 3216 mg/kg bodyweight Animal: rabbit, Animal sex: male, 95% CL: 2373 - 4350

Isoamyl alcohol (123-51-3)	
LC50 Inhalation - Rat (Vapours)	10 mg/l Source: ECHA

Acetic acid (64-19-7)	
LD50 oral rat	3310 mg/kg bodyweight Animal: rat
LD50 oral	4960 mg/kg bodyweight Animal: mouse
LD50 dermal rabbit	1060 mg/kg Source: HSDB, NITE
LC50 Inhalation - Rat [ppm]	16000 ppm Source: ChemIDPlus

Propionic acid (79-09-4)	
LD50 oral rat	3455.1 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity), 95% CL: 2978,9 - 4007,5
LD50 dermal rat	3235 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
LD50 dermal rabbit	3235 mg/kg Source: ECHA
LC50 Inhalation - Rat	> 20 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity)
LC50 Inhalation - Rat (Vapours)	> 20 mg/l Source: ECHA

n-butyl acetate (123-86-4)	
LD50 oral rat	3200 ml/kg Source: ECHA
LD50 dermal rabbit	> 17600 mg/kg Source: ECHA
LC50 Inhalation - Rat (Vapours)	1802 mg/l Source: ECHA

ethyl acetate (141-78-6)	
LD50 oral	4934 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
LD50 dermal rabbit	> 20000 mg/kg bodyweight Animal: rabbit, Animal sex: male

Isoamyl acetate / Isopentyl acetate (123-92-2)	
LD50 dermal rabbit	> 5000 mg/kg bodyweight Animal: rabbit

Skin corrosion/irritation : Not classified (Based on available data, the classification criteria are not met)
pH: 3.6 (2.6 – 4.6)

Acetic acid (64-19-7)	
pH	2.4 Source: ECHA

n-butyl acetate (123-86-4)	
pH	6.2 Temp.: 20 °C Concentration: (≈)5 g/L

Serious eye damage/irritation : Causes serious eye irritation.
pH: 3.6 (2.6 – 4.6)

Acetic acid (64-19-7)	
pH	2.4 Source: ECHA

n-butyl acetate (123-86-4)	
pH	6.2 Temp.: 20 °C Concentration: (≈)5 g/L

Respiratory or skin sensitisation : Not classified (Based on available data, the classification criteria are not met)

Germ cell mutagenicity : Not classified (Based on available data, the classification criteria are not met)

Carcinogenicity : Not classified (Based on available data, the classification criteria are not met)

ethanol/ ethyl alcohol (64-17-5)	
IARC group	1 - Carcinogenic to humans

Reproductive toxicity : Not classified (Based on available data, the classification criteria are not met)

STOT-single exposure : Not classified (Based on available data, the classification criteria are not met)

butan-1-ol; n-butanol (71-36-3)	
STOT-single exposure	May cause respiratory irritation. May cause drowsiness or dizziness.

Isoamyl alcohol (123-51-3)	
STOT-single exposure	May cause respiratory irritation.

Propionic acid (79-09-4)	
STOT-single exposure	May cause respiratory irritation.

n-butyl acetate (123-86-4)	
STOT-single exposure	May cause drowsiness or dizziness.

ethyl acetate (141-78-6)	
STOT-single exposure	May cause drowsiness or dizziness.

STOT-repeated exposure : Not classified (Based on available data, the classification criteria are not met)

butan-1-ol; n-butanol (71-36-3)	
LOAEL (oral, rat, 90 days)	500 mg/kg bodyweight Animal: rat
NOAEL (oral, rat, 90 days)	125 mg/kg bodyweight Animal: rat

ethanol/ ethyl alcohol (64-17-5)	
LOAEL (oral, rat, 90 days)	3200 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)
NOAEL (oral, rat, 90 days)	1730 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents), Remarks on results: other:
NOAEL (subchronic, oral, animal/male, 90 days)	< 9700 mg/kg bodyweight Animal: mouse, Animal sex: male, Guideline: EPA OPPTS 870.3100 (90-Day Oral Toxicity in Rodents)
NOAEL (subchronic, oral, animal/female, 90 days)	> 9400 mg/kg bodyweight Animal: mouse, Animal sex: female, Guideline: EPA OPPTS 870.3100 (90-Day Oral Toxicity in Rodents)

Isoamyl alcohol (123-51-3)	
NOAEL (oral, rat, 90 days)	1250 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)

Acetic acid (64-19-7)	
NOAEL (oral, rat, 90 days)	290 mg/kg bodyweight Animal: rat, Animal sex: male

ethyl acetate (141-78-6)	
LOAEL (oral, rat, 90 days)	3600 mg/kg bodyweight Animal: rat, Guideline: EPA OTS 795.2600 (Subchronic Oral Toxicity Test)
NOAEL (oral, rat, 90 days)	900 mg/kg bodyweight Animal: rat, Guideline: EPA OTS 795.2600 (Subchronic Oral Toxicity Test)

Isoamyl acetate / Isopentyl acetate (123-92-2)	
NOAEL (subchronic, oral, animal/female, 90 days)	443.07 mg/kg bodyweight Animal: , Animal sex: female

Aspiration hazard : Not classified (Based on available data, the classification criteria are not met)

butan-1-ol; n-butanol (71-36-3)	
Viscosity, kinematic	3.641 mm²/s

ethanol/ ethyl alcohol (64-17-5)	
Viscosity, kinematic	1.488 mm²/s

Isoamyl alcohol (123-51-3)	
Viscosity, kinematic	5.32 mm²/s Temp.: '20°C' Parameter: 'kinematic viscosity (in mm²/s)'

Acetic acid (64-19-7)	
Viscosity, kinematic	1.015 mm²/s

n-butyl acetate (123-86-4)	
Viscosity, kinematic	0.83 mm²/s Temp.: '20°C' Parameter: 'kinematic viscosity (in mm²/s)'

Isoamyl acetate / Isopentyl acetate (123-92-2)	
Viscosity, kinematic	1.176 mm²/s

11.2. Information on other hazards

No additional information available

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.

Hazardous to the aquatic environment, short–term (acute) : Not classified (Based on available data, the classification criteria are not met)

Hazardous to the aquatic environment, long–term (chronic) : Not classified (Based on available data, the classification criteria are not met)

butan-1-ol; n-butanol (71-36-3)	
LC50 - Fish [1]	1376 mg/l Test organisms (species): Pimephales promelas
EC50 - Crustacea [1]	1328 mg/l Test organisms (species): Daphnia magna
EC50 96h - Algae [1]	225 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
NOEC (chronic)	4.1 mg/l Test organisms (species): Daphnia magna Duration: '21 d'

ethanol/ ethyl alcohol (64-17-5)	
LC50 - Fish [1]	14.2 g/l Test organisms (species): Pimephales promelas
EC50 - Crustacea [1]	> 10000 mg/l Test organisms (species): Daphnia magna
EC50 96h - Algae [1]	≈ 22000 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
ErC50 algae	275 mg/l Source: ECHA
NOEC (chronic)	9.6 mg/l Test organisms (species): Daphnia magna Duration: '9 d'

Isoamyl alcohol (123-51-3)	
LC50 - Fish [1]	700 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)
EC50 - Crustacea [1]	255 mg/l Test organisms (species): Daphnia magna

Isoamyl alcohol (123-51-3)	
EC50 72h - Algae [1]	> 500 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)
EC50 72h - Algae [2]	493 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)
EC50 96h - Algae [1]	274 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)
EC50 96h - Algae [2]	181 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)

Acetic acid (64-19-7)	
LC50 - Fish [1]	> 1000 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)
LC50 - Fish [2]	> 300.82 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)
EC50 - Crustacea [1]	> 1000 mg/l Test organisms (species): Daphnia magna
EC50 - Crustacea [2]	> 300.82 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	> 1000 mg/l Test organisms (species): Skeletonema costatum
EC50 72h - Algae [2]	> 300.82 mg/l Test organisms (species): Skeletonema costatum

Propionic acid (79-09-4)	
LC50 - Fish [1]	> 10000 mg/l Test organisms (species): Leuciscus idus
EC50 - Crustacea [1]	> 500 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	> 500 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)

n-butyl acetate (123-86-4)	
LC50 - Fish [1]	18 mg/l Test organisms (species): Pimephales promelas
EC50 - Crustacea [1]	44 mg/l Test organisms (species): Daphnia sp.
EC50 - Other aquatic organisms [1]	32 mg/l Test organisms (species): Artemia salina
EC50 72h - Algae [1]	674.7 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)
NOEC (chronic)	23 mg/l Test organisms (species): Daphnia magna Duration: '21 d'

ethyl acetate (141-78-6)	
LC50 - Fish [1]	230 mg/l Test organisms (species): Pimephales promelas
NOEC (chronic)	2.4 mg/l Test organisms (species): Daphnia magna Duration: '21 d'

Isoamyl acetate / Isopentyl acetate (123-92-2)	
LC50 - Fish [1]	22 – 46 mg/l Test organisms (species): Danio rerio (previous name: Brachydanio rerio)
EC50 - Crustacea [1]	42 mg/l Test organisms (species): other:Daphnia magna STRAUS

12.2. Persistence and degradability

ORGANIC MANGO FLAVOUR MA-0449	
Persistence and degradability	Not rapidly degradable

butan-1-ol; n-butanol (71-36-3)	
Persistence and degradability	Not rapidly degradable

ethanol/ ethyl alcohol (64-17-5)	
Persistence and degradability	Not rapidly degradable

Isoamyl alcohol (123-51-3)	
Persistence and degradability	Not rapidly degradable

Acetic acid (64-19-7)	
Persistence and degradability	Not rapidly degradable

Propionic acid (79-09-4)	
Persistence and degradability	Not rapidly degradable

n-butyl acetate (123-86-4)	
Persistence and degradability	Not rapidly degradable

ethyl acetate (141-78-6)	
Persistence and degradability	Not rapidly degradable

Isoamyl acetate / Isopentyl acetate (123-92-2)	
Persistence and degradability	Not rapidly degradable

12.3. Bioaccumulative potential

ethanol/ ethyl alcohol (64-17-5)	
Partition coefficient n-octanol/water (Log Pow)	-0.32 Source: ICSC

Isoamyl alcohol (123-51-3)	
Partition coefficient n-octanol/water (Log Pow)	1.16 Source: HSDB

Acetic acid (64-19-7)	
Partition coefficient n-octanol/water (Log Pow)	-0.17 Source: ECHA

Propionic acid (79-09-4)	
Partition coefficient n-octanol/water (Log Pow)	0.33 Source: HSDB

n-butyl acetate (123-86-4)	
Partition coefficient n-octanol/water (Log Pow)	1.78 Source: HSDB

Isoamyl acetate / Isopentyl acetate (123-92-2)	
Partition coefficient n-octanol/water (Log Pow)	2.13 Source: ICSC

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Endocrine disrupting properties

No additional information available

12.7. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

Additional information : Flammable vapours may accumulate in the container.

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA

ADR	IMDG	IATA
14.1. UN number or ID number		
UN 1197	UN 1197	UN 1197
14.2. UN proper shipping name		
EXTRACTS, LIQUID	EXTRACTS, LIQUID	Extracts, liquid
Transport document description		
UN 1197 EXTRACTS, LIQUID, 3, III, (D/E)	UN 1197 EXTRACTS, LIQUID, 3, III	UN 1197 Extracts, liquid, 3, III
14.3. Transport hazard class(es)		
3	3	3
		
14.4. Packing group		
III	III	III
14.5. Environmental hazards		
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No EmS-No. (Fire): F-E EmS-No. (Spillage): S-D	Dangerous for the environment: No
No supplementary information available		

14.6. Special precautions for user

Overland transport

Classification code (ADR) : F1
Special provisions (ADR) : 601
Limited quantities (ADR) : 5l
Excepted quantities (ADR) : E1
Packing instructions (ADR) : P001, IBC03, LP01, R001
Mixed packing provisions (ADR) : MP19
Portable tank and bulk container instructions (ADR) : T2
Portable tank and bulk container special provisions (ADR) : TP1
Tank code (ADR) : LGBF
Vehicle for tank carriage : FL
Transport category (ADR) : 3
Special provisions for carriage - Packages (ADR) : V12
Special provisions for carriage - Operation (ADR) : S2

Hazard identification number (Kemler No.)	:	30
Orange plates	:	
Tunnel restriction code (ADR)	:	D/E
EAC code	:	3YE

Transport by sea

Special provisions (IMDG)	:	223, 955
Limited quantities (IMDG)	:	5 L
Excepted quantities (IMDG)	:	E1
Packing instructions (IMDG)	:	P001, LP01
IBC packing instructions (IMDG)	:	IBC03
Tank instructions (IMDG)	:	T2
Tank special provisions (IMDG)	:	TP1
Stowage category (IMDG)	:	A
Properties and observations (IMDG)	:	Usually consist of alcoholic solutions. Miscibility with water depends upon the composition.

Air transport

PCA Excepted quantities (IATA)	:	E1
PCA Limited quantities (IATA)	:	Y344
PCA limited quantity max net quantity (IATA)	:	10L
PCA packing instructions (IATA)	:	355
PCA max net quantity (IATA)	:	60L
CAO packing instructions (IATA)	:	366
CAO max net quantity (IATA)	:	220L
Special provisions (IATA)	:	A3
ERG code (IATA)	:	3L

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU-Regulations

REACH Annex XVII (Restriction List)

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Contains substance(s) listed on the REACH Candidate List < 0.1% or SCL.

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (2024/590)

Not listed on the Ozone Depletion list (Regulation EU 2024/590)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 2024/590 on substances that deplete the ozone layer)

Council Regulation (EC) for the control of dual-use items

Contains no substance subject to the COUNCIL REGULATION (EC) for the control of dual-use items

Explosives Precursors Regulation (EU 2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

Drug Precursors Regulation (EC 273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Abbreviations and acronyms:	
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BLV	Biological limit value
BOD	Biochemical oxygen demand (BOD)
COD	Chemical oxygen demand (COD)
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC-No.	European Community number
EC50	Median effective concentration
EN	European Standard
IARC	International Agency for Research on Cancer(IARC)
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Lethal concentration for 50% of the population tested (median lethal concentration)
LD50	Median lethal dose for 50% of the population tested (median lethal dose)
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
OEL	Occupational Exposure Limit
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet

Abbreviations and acronyms:	
STP	Sewage treatment plant
ThOD	Theoretical oxygen demand (ThOD)
TLM	Median Tolerance Limit
VOC	Volatile Organic Compounds
CAS-No.	Chemical Abstracts Service number
N.O.S.	Not Otherwise Specified
vPvB	Very Persistent and Very Bioaccumulative
ED	Endocrine disruptor

Full text of H- and EUH-statements:	
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Chronic 3	Hazardous to the aquatic environment – Chronic Hazard, Category 3
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
Skin Corr. 1A	Skin corrosion/irritation, Category 1, Sub-Category 1A
Skin Corr. 1B	Skin corrosion/irritation, Category 1, Sub-Category 1B
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Respiratory tract irritation
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.